


# Raychem HIQ

## MINERAL INSULATED (MI) INCONEL SHEATHED HEATING CABLE

### TYPICAL CABLE CONSTRUCTIONS



Raychem HIQ mineral insulated (MI) Inconel 600 series heating cables are suited for use in hazardous areas. The Inconel 600 sheath offers excellent corrosive properties against a wide range of organic acids and alkalis, as well as chloride stress-corrosion cracking, in combination with a high temperature withstand capability. HIQ cables are typically used in bitumen plants, gas plants, oil refineries, reactors and vessels, sodium loops and a wide variety of other heat-tracing applications where temperature resistance, power output and durability are required and exceed the limitations of stainless steel sheathed MI heating cables. The heating cables can be used for exposure temperatures up to 700°C and a typical power output up to 300 W/m. Higher temperatures and power outputs can be achieved, contact Pentair for assistance. The heating cables are offered as bulk cables as well as factory-terminated heating units employing brazing or laser welding techniques to ensure optimum quality of the connections. The offering is completed with a full range of components for installation, connection and splicing of the heating cables.

### APPLICATION

Area classification	Hazardous areas, Zone 1 or Zone 2 (Gas) or Zone 21 or zone 22 (Dust) Ordinary areas
---------------------	--

### APPROVALS

System (heating units)	Baseefa02ATEX0046X  II 2GD Ex e II T6 to T1 Ex tD A21 IP6X Actual T class temperature determined by design  TC RU C-BE.MI062.B.02787 1 Ex e II T6...T1 Gb X Ex td A21 IP66 T6...T1
------------------------	---

Bulk cable	Baseefa02ATEX0045U  II 2G Ex e II  TC RU C-BE.ME92.B.00056 1 Ex e II T6...T1 Gb X Ex td A21 IP66 T6...T1
------------	--

**TECHNICAL DATA**

Cable sheath material	Inconel 600		
Conductor material	Nichrome		
Max. exposure temperature	450°C (brazed heating units) 700°C* (laser welded heating units) *Higher temperatures can be realized, contact Pentair		
=Min. installation temperature	-60°C		
Min. bending radius	6 x outer diameter at -60°C		
Max. supply voltage and power	Voltage (U <sub>0</sub> /U)	Max. power output*	
	300/500 Vac	300 W/m	
	460/800 Vac (laser welded heating units)	*typical value, depending on application	
Earth leakage	3 mA/100 m (nominal at 20°C)		
Min. cable spacing	25 mm for hazardous areas		

**MI SERIES HEATING CABLES HIQ**

Order Reference	Nominal resistance (Ω/km @ 20°C)	Outer diameter (mm)	Temp. coefficient (x 10 <sup>-3</sup> /K)	Max. coil length [m]	Nom. weight (kg/km)
HIQ1M10K	10000	3.2	0.09	772	39
HIQ1M6300	6300	3.2	0.09	774	39
HIQ1M4000	4000	3.2	0.09	776	39
HIQ1M2500	2500	3.4	0.09	689	46
HIQ1M1600	1600	3.6	0.09	617	52
HIQ1M1000	1000	3.9	0.09	528	62
HIQ1M630	630	4.3	0.09	437	78
HIQ1M400	400	4.7	0.09	368	96
HIQ1M250	250	5.3	0.09	292	127
HIQ1M160	160	6.5	0.09	194	191

**RECOMMENDED COLD LEADS FOR HIQ MI SERIES HEATING CABLES**

Nom. cross section [mm <sup>2</sup> ]	Order reference	Max. current (design B)	Outer diameter (mm)	Standard gland size
2.5	IC1H2.5	34	4.9	M20
2.5	AC1H2.5	34	5.3	M20
6	IC1H6	57	6.4	M20
6	AC1H6	57	6.4	M20

Brass glands are standard on all heating units. Other materials are possible, contact Pentair for more information. Delivery length of bulk cable on coil depends on type of resistance and is limited by max. coil length as indicated in the table on top. Factory terminated elements are limited by a max. weight of 50kg, however to ensure practical and safe on-site handling, it is strongly recommended to limit element lengths to 25 - 30kg. Not all resistances are standard items and as such may not be in stock. Contact Pentair to confirm lead time. Pentair requires the use of a 30 mA residual current device to provide maximum safety and protection from fire.

Where design results in higher leakage current, the preferred trip level for adjustable devices is 30 mA above any inherent capacitive leakage characteristic of the heater as specified by the trace heater supplier or alternatively, the next common available trip level for non adjustable devices, with a maximum of 300 mA. All safety aspects need to be proven.

Also refer to the components section for more details on heating units, accessories and nomenclatures.

**MI HEATING CABLE SHEATH CORROSION RESISTANCE AND TEMPERATURE DATA**

Sheath Material	Description	Sulphuric Acid	Hydrochloric Acid	Hydrofluoric Acid	Phosphoric Acid	Nitric Acid	Organic Acid	Alkalis	Sea Water	Chloride
Inconel 600 DIN 2.4816	High nickel, high chromium content inconel alloy 600	X	X	A	X	X	GE	GE	A	GE

Note: NR Not recommended, A acceptable, GE Good to excellent, X Check for specific data

Temperature limitation based on construction of heating element.

Corrosion resistance data is dependent on temperature and concentration.



[WWW.PENTAIRTHERMAL.COM](http://WWW.PENTAIRTHERMAL.COM)

**EUROPE, MIDDLE EAST, AFRICA**

Tel: +32.16.213.511  
Fax: +32.16.213.603  
[thermal.info@pentair.com](mailto:thermal.info@pentair.com)

**UNITED KINGDOM**

Tel: 0800 969 013  
Fax: 0800 968 6241  
[salesthermaluk@pentair.com](mailto:salesthermaluk@pentair.com)

**IRELAND**

Tel: 1800 654 241  
Fax: 1800 654 240  
[salesie@pentair.com](mailto:salesie@pentair.com)

Pentair is owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

© 1998-2016 Pentair.